



Transported by Passion



Silage Transport Trailers

SLW

SLW 25

Load volume 27 cubic metres



SLW 30

Load volume 32 cubic metres



SLW 40

Load volume 38 cubic metres





Transported by Passion



SLW 45 / SLW 45 TL

Load volume 42 cubic metres Load volume 46 cubic metres



SLW 45 TR

Load volume 46 cubic metres



SLW 50

Load volume 50 / (60 cubic metres)



HAWE SLW are also available on **WPS body swap systems** in various dimensions with tandem or tridem chassis. Much higher utilization due to several different HAWE bodies.

Silage Transport Trailers SLW



Electro-hydraulic control from the driver cabin available from HAWE upon request.



Hydraulically folding front wall

All HAWE silage transport trailers feature a transparent front wall with a hydraulically folding upper section.



Hydraulic height-adjustable side walls for increasing transport volume.



Labelling

Standard tailgate opening label at the front of the forage harvester.



Automatic chain tensioner

Visual monitoring of automatic chain tensioner.



HAWE Silage Transport Trailers

are designed for professional use, high loads and a long service life. These trailers, which are available in seven models from 27 to 50 (60) cubic metres loading volume, were developed in close cooperation with leading customers. Each HAWE silage transport trailer represents decades of experience. All trailers feature important details to deliver maximal loading volumes and make working with them as easy as possible for users.



Transported by Passion



Hood-type end profile

New top flange designed as a hood-type profile to prevent trickle loss.



Cargo area spotlight / camera system

A powerful LED spotlight inside is installed as standard to ensure that loading and unloading processes can be optimally monitored even in poor light conditions. HAWE supplies camera systems for internal and rear view as option.



Tailgate

Extended, tightly sealing tailgate to prevent trickle loss.

Silage Transport Trailers SLW



Large-volume tyres reduce the tractive power requirement and prevent soil compaction even under wet harvesting conditions. The large contact area minimises rolling resistance to keep the tyres rolling even under difficult conditions.

Lift axle for increased traction under difficult conditions and reduced rolling resistance during road travel.



Outstanding stability due to the wide chassis and low centre of gravity.



Running gear with hydro-pneumatic suspension.



HAWE Silage Transport Trailers

HAWE silage transport trailers are very easy to tow, highly fuel-efficient and gentle to soils. HAWE offers all popular commercial coupling systems for upper and lower attachment. Drawbar suspension is provided as standard in all models except the SLW 25 TD; hydro-pneumatic suspension is available in the SLW 40 to SLW 50 models.



Transported by Passion



HAWE Cover Load compartment cover with hydraulic drive. For safe, lossless road transport. (Equipment)



Large service opening
Large access hatch to the cargo area with folding ladder.



Hydraulic parking stand and hydro-pneumatic drawbar suspension.



Positive steering control via a Bowden cable.



Transported by Passion

Specifications

Type	SLW 25	SLW 30	SLW 40 SLW-A 40	SLW 45 SLW-A 45	SLW 45 TL	SLW 45 TR SLW-A 45	SLW 50 SLW-A 50
Permitted gross weight (t)	14	18	20	23	24	30	33
Capacity (m ³)	27	32	38	42	46	46	50 (60)
Body dimensions							
Length (m)	6,00	6,70	7,20	7,95	8,50	8,50	9,35
Width (m)	2,10	2,30	2,30	2,30	2,30	2,30	2,30
Height (m)	2,10	2,10	2,30	2,30	2,30	2,30	2,30
Dosierwalze(n)	Option	2	2	2	2	2	2
Gesamtabmessung							
Length (m)	8,05	8,65	8,95	9,65	10,50	10,50	11,30
Width incl. tyres (m)	2,50	2,55	2,75	2,85	2,85	2,75	2,85
Height (m)	3,00	3,70	4,00	4,00	4,00	4,00	4,00
Running gear type	Tandem	Tandem	Tandem	Tandem	Tandem	Tridem	Tridem
Suspension	24 t LK float unit with dynamic axle compensation	24 t LK float unit with dynamic axle compensation	32 t LK float unit with dynamic axle compensation	32 t LK float unit with dynamic axle compensation	Hydro-pneumatic running gear suspension with lift axle	36 t LK float unit with dynamic axle compensation	48 t LK float unit with dynamic axle compensation
Steering axle(s)	Optional	Self-steering	Self-steering	Self-steering	Self-steering	1st + 3rd axle Self-steering	1st + 3rd axle Self-steering
Attachment							
above	Standard	Standard	Serie	-	-	-	-
below	Optional	Optional	Optional	Standard	Standard	Standard	Standard
Drawbar suspension	Optional	Standard	Standard	Standard	Hydraulic	Standard	Hydraulic
Tyres							
Standard	560/60 R 22,5	600/50 R 22,5	650/55 R 26,5	710/50 R 26,5	710/50 R 26,5	710/50 R 26,5	710/50 R 26,5

Standard features: From SLW 30 TN: Steel body, steel floor, side access hatch with ladder, self-steering BPW axle(s), wide-angle drive shaft with overload protection, interior spotlight, dual-circuit air brakes with automatic load-dependent braking force regulator (ALB), drawbar suspension, heavy parking stand, hydraulic parking stand in models SLW 45 and above.

Additional equipment: hydraulic positive steering, lift axle, hydraulic wall extension, cargo area cover, range of tyre options. Models SLW 40 TN and above are also available as swap body systems, with hydro-pneumatic running gear and drawbar suspension. All popular commercial coupling systems for upper and lower attachment are available.

HAWE is constantly updating its product range. We reserve the right to alter technical specifications, prices and models at any time.

Illustrations and specifications are only approximate and not binding.

HAWE Wester GmbH & Co. KG
 Zum Turm 16 · 26892 Wipplingen
 Phone +49 (0)4966 / 91880 · Fax +49 (0)4966 / 1211
 mail@HAWE-wester.de · www.HAWE-wester.de