



Transported by Passion



Silage Transport Trailers **SLW**



Transportieren mit Leidenschaft

SLW 30

Load volume 32 / 36 cubic metres



SLW 35

Load volume 36 / 39 cubic metres



SLW 40 / SLW-A 40

Load volume 39 / 42 cubic metres



SLW 45

Load volume 42 / 45 cubic metres



SLW 50

Load volume 48 / 52 cubic metres



HAWE SLW are also available on **WPS body swap systems** with tandem chassis.
Much higher utilization due to several different HAWE bodies.

www.hawe-wester.de



Transportieren mit Leidenschaft

Silage Transport Trailers SLW



Electro-hydraulic control from the driver cabin available from HAWE upon request.



Hydraulically folding front wall

All HAWE silage transport trailers feature a transparent front wall with a hydraulically folding upper section.



Hood-type end profile

New top flange designed as a hood-type profile to prevent trickle loss.



LED light strips / camera system

A powerful LED light strips inside is installed as standard to ensure that loading and unloading processes can be optimally monitored even in poor light conditions. HAWE supplies camera systems for internal and rear view as option.



Labelling

Standard tailgate opening label at the front of the forage harvester.



Automatic chain tensioner

Visual monitoring of automatic chain tensioner.



New tailgate design

Increased ground clearance for the most extreme operating conditions. Raised tail lights to protect against damage and dirt.

HAWE Silage Transport Trailers

are designed for professional use, high loads and a long service life. These trailers, which are available in seven models from 32 to 52 cubic metres loading volume, were developed in close cooperation with leading customers. Each HAWE silage transport trailer represents decades of experience. All trailers feature important details to deliver maximal loading volumes and make working with them as easy as possible for users.

www.hawe-wester.de



Transportieren mit Leidenschaft

Silage Transport Trailers SLW



Large service opening

Large access hatch to the cargo area with folding ladder.



Hydraulic parking stand and hydro-pneumatic drawbar suspension.



Positive steering control via a Bowden cable.



HAWE Cover Load compartment cover with hydraulic drive. For safe, lossless road transport. (Equipment)



Hydraulic articulated drawbar

increased ground clearance for the most extreme operating conditions. (Option on SLW 40 / SLW 45 / SLW 50 models) overfill

Large-volume tyres reduce the tractive power requirement and prevent soil compaction even under wet harvesting conditions. The large contact area minimises rolling resistance to keep the tyres rolling even under difficult conditions.



Lift axle for increased traction under difficult conditions and reduced rolling resistance during road travel.



Running gear with hydro-pneumatic suspension.

HAWE Silage Transport Trailers

HAWE silage transport trailers are very easy to tow, highly fuel-efficient and gentle to soils.

Drawbar suspension is provided as standard in all models, hydro-pneumatic suspension is available in the SLW 40 to SLW 50 models.

www.hawe-wester.de



Transported by Passion

Specifications

Type	SLW 30	SLW 35	SLW 40 / SLW-A 40	SLW 45	SLW 50
Permitted gross weight (t)	18	20 or 23	20 or 23	24	33
Capacity (m³)	32	36	39	42	48
Capacity with increase 200 mm (m³)	36	39	42	45	52
Body dimensions					
Length (m)	6,70	7,45	7,95	8,50	9,85
Width (m)	2,30	2,30	2,30	2,30	2,30
Height (m)	2,10	2,10	2,10	2,10	2,10
Metering roll(s)	2	2	2	2	2
Overall dimension					
Length (m)	8,65	9,20	9,65	10,50	11,80
Width incl. tyres (m)	2,55	2,85	2,85	2,85	2,85
Height (m)	3,70	4,00	4,00	4,00	4,00
Running gear type BPW axle	Tandem	Tandem	Tandem	Tandem	Tridem
Brakes	Dual-circuit air brakes with ALB				
Suspension	24 t LK float unit with dynamic axle compensation		32 t LK float unit with dynamic axle compensation		48 t LK float unit with dynamic axle compensation
	Hydraulic axle compensation with suspension and lifting axle optional				
Dist. between axles (mm)	1550	1550 / 1810	1550 / 1810	1810	1810
Steering axle(s), self-steering	Optional	Standard	Standard	Standard	Optional
Forced steering	Optional	Optional	Optional	Optional	Standard
Attachment					
Max. drawbar load (t)	2	3	3	4	4
Upper drawbareye, 40mm	Serie	Optional	Optional	-	-
Bottom K80	Optional	Standard	Standard	Standard	Standard
Drawbar suspension	Mechanical	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Articulated drawbar	-	Optional	Optional	Optional	Optional
Tyres					
Standard	600/50 R 22,5	710/50 R 26,5	710/50 R 26,5	710/50 R 26,5	710/50 R 26,5
Optional	710/50 R 26,5	710/50 R 30,5	800/45 R 30,5	800/45 R 30,5	800/45 R 30,5

Standard features: Steel body, steel floor, side access hatch with ladder, self-steering BPW axle(s), wide-angle drive shaft with overload protection, LED light bar inside.

Additional equipment: hydraulic positive steering, cargo area cover, Wheels up to 30.5". SLW 40 are also available as swap body systems, HAWE is constantly updating its product range. We reserve the right to alter technical specifications, prices and models at any time. Illustrations and specifications are only approximate and not binding.

HAWE Wester GmbH & Co. KG
 Zum Turm 16 · 26892 Wippeningen
 Phone +49 (0)4966 / 91880 · Fax +49 (0)4966 / 1211
 mail@HAWE-wester.de · www.HAWE-wester.de